

Spill Ring Series

Close-to-Ceiling

HOTCD, HOTCDO, HOTSFD



HOTCD



HOTCDO



HOTSFD

FEATURES & SPECIFICATIONS

Stylish ceiling/wall mounted luminaire in either white or walnut finish with a variety of lamp combinations and sizes enhanced by linear sided acrylic diffuser. Designed for baths, kitchens, rec rooms, corridors, aisles, stairwells, over or bedside mirrors, over bulletin boards, in vanities, and displays.

MOUNTING

Back plate provided with adequate knockouts and mounting holes for either wall or ceiling installation.

CONSTRUCTION

All metal parts are die-formed from heavy gauge cold roll steel with overlapping end caps to ensure uniformity and dimensional stability. One light and two light units same external dimensions.

DIFFUSER

Linear sided prismatic lens of extruded acrylic for controlled light.

WIRING

Standard Ballast are 120 Volts & 60 hertz.

LISTING

Fixtures conform to Underwriters' Laboratories standards for production and are carefully tested prior to packing. UL damp Listed.

MODEL NO.	SIZE (L x W x H)	LAMPING
HOTCD118SNLN	10" x 10" x 4.25"	(1) 18W QUAD 4 PIN
HOTCD218SNLN	14" x 14" x 4.25"	(2) 18W QUAD 4 PIN
HOTCD226SSLN	17.75" x 17.75" x 4.25"	(2) QUAD 26W 4 PIN 4000k (Included)
HOTCDO232SSN	32.3" x 18.1" x 4.25"	(2) FC12T9 (32W CIRC)
HOTSFD122SSN	14.1" x 14.1" x 4.25"	(1) FCT9 (22W CIRC)

Consult Factory for bronze versions and other lamping options.
Consult Factory for Emergency Option.