


# Pocket Acorn

APW Series

## FEATURES & SPECIFICATIONS

- Decorative Wall Mount Pocket Lanterns
- Available in Black or White with Photocel Available on select fixtures
- Molded of durable non -corrosive UV Resistant Plastic
- UL Listed for Wet Location
- Acrylic Diffuser



## LED SPECIFICATION

- 120-277 Input Voltage, 50/60Hz
- Constant current at 700mA
- Class 2 Driver Power Factor >.9
- Ambient Operating Temperature -40°C (-40°F) to +40°C (105°F)
- Estimated 50,000 HRS L<sub>70</sub>
- Thermally protected LED Array

Item Number	Dimensions ( L x W x H )	Lamping
APW123GUWH	6.0" x 7.0" x 9.0"	1-23W GU MAX
APWL11W912L40K	6.0" x 7.0" x 9.0"	4 CREE LED 1W, 912 Lumens, 4000K

### L900C LED REPLACEMENT PARTS

L09C-DC-700-04-R = 11 CREE LED ARRAY

IG900-DMV-1 = LED DRIVER

\* Data Per LM79/LM80/TM21 Available upon request.

\*\*Estimated from LED Source

NOTE: Specifications and dimensions subject to change without notice. Consult your Texas Fluorescent Lighting Representative for availability and ordering information.

Texas Fluorescents

2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 Fax: 972-247-0200

www.texasfluorescents.com email: sales@texasfluorescents.com

Catalog Number:

Notes: