

CIT LED Series

Harsh Environment Enclosure

CITADEL LED lighting is designed for parking garages and other applications where weatherproof wide area lighting is required. A highly engineered LED lighting system is coupled with the best weather proofing materials and design to provide the most durable lighting system in the industry. Poured in place gasket and cam latches seal the enclosures. The mounting can provide dramatic savings on installation labor. Designed around a long lasting and efficient LED array with specially designed heat sinks, reflectors and retaining clips ensure maximum LED life and wide spread lighting to put the light exactly where you want it. A specially designed driver to compliment the LED arrays housed in special enclosure to ensure effective heat dissipation and easy maintenance Very tough diffuser resists breakage and are also specially designed to provide excellent light transmission of the LEDs while minimizing the glare from the bright LED's.



SIZE W x L X H in inches

2ft: 7.33W x 27.68L x 4.13H

4ft: 7.33W x 51.81L x 4.13H

8ft: 7.33W x 98.51L x 4.13H

ORDERING INFORMATION

CITADEL 2'

Example: **CIT24LRFS24W2400LDMV40K**

STANDARD

CIT24L	RF	S24W2400L	DMV	40K	
Series		Wattage/Lumens	Driver	Kelvin Temperature	Accessories
CIT24L LED 2' Vaportight		S24W2400L 24 System Watts, 2400 Delivered Lumens	DMV 0-10V	30K 3000K	See Accessories Page
		S28W2750L 28 System Watts, 2750 Delivered Lumens	MV Multi-Volt 120-277V	35K 3500K	
	Lens			40K 4000K	
	RF Ribbed Frosted			50K 5000K	
	LB Ribbed Clear				
	FR Smooth Frosted				
	OL Smooth Clear				

High Output

CIT24L	RF	H36W3500L	DMV	40K	
Series		Wattage/Lumens	Driver	Kelvin Temperature	Accessories
CIT24L LED 2' Vaportight		H36W3500L 36 System Watts, 3500 Delivered Lumens	DMV 0-10V	30K 3000K	See Accessories Page
			MV Multi-Volt 120-277V	35K 3500K	
	Lens			40K 4000K	
	RF Ribbed Frosted			50K 5000K	
	LB Ribbed Clear				
	FR Smooth Frosted				
	OL Smooth Clear				

