

Heavy duty die-cast aluminum powder coating construction with high impact polycarbonate lens are available in Round or Square in two sizes. Silicone rubber included to prevent any leakage from the outside 1/2" tapped holes available for installing photocell (optional). Ideal for parking garages, walkways, and other harsh environments.

FEATURES & SPECIFICATIONS

- Energy Saving
- Multi-volt
- Die Cast Housings
- Clear Polycarbonate Lens
- Borosilicate Glass Lens with Hinged Door
- Bulbs Included
- Bronze Powder Coat Finish
- Black Neoprene Gasket
- Wet Location
- UL Listed

OPTIONS


- Photocell
- Tamper Resistant Screws
- White or Custom Paint



SQUARE
CV200
CV300



ROUND
CV400
CV500



ORDERING INFORMATION

EX: DC150-150HPS-120-LP

Item Number	Dimensions	Lamping
CV20070HPS120LP	7.5" x 8" x 8"	70 Watt High Pressure Sodium
CV20070MH120LP	7.5" x 8" x 8"	70 Watt Metal Halide
CV200PL26MVLP	7.5" x 8" x 8"	(1) 26 Watt TTT - 4 Pin
CV200PL42MVLP	7.5" x 8" x 8"	(1) 42 Watt TTT - 4 Pin
CV300150MHMTLP	8.75" x 12.4" x 12.4"	1500 Watt Metal Halide
CV3002PL42MVLP	8.75" x 12.4" x 12.4"	(2) 42 Watt TTT - 4 Pin
CV40070HPS120LP	11.5" x 11.5" x 7.4"	70 Watt High Pressure Sodium
CV40070MH120LP	11.5" x 11.5" x 7.4"	70 Watt Metal Halide
CV400PL26MVLP	11.5" x 11.5" x 7.4"	(1) 26 Watt TTT - 4 Pin
CV400PL42MVLP	11.5" x 11.5" x 7.4"	(1) 42 Watt TTT - 4 Pin
CV500150HPS120LP	15" x 15" x 7.9"	150 Watt High Pressure Sodium
CV500150MHMTLP	8.75" x 12.4" x 12.4"	150 Watt Metal Halide
CV5002PL42MVLP	8.75" x 12.4" x 12.4"	(2) 42 Watt TTT - 4 Pin
CV300L35W3501L50K*	8.75" x 12.4" x 12.4"	28 Cree LED, 35W, 3501 Lumens, 5000K

*DLC Approved



Catalog Number:

Notes:

LED vs. HID VANDELIER					
Wall Pack Light Source	Input Wattage	Lifespan Hrs/Yrs	Energy Use (24hrs/day) Annual	Annual Cost (maintenance + electricity) @ 50.11 / kWh	Electrical Cost Savings
HID	165	24,000 / 2.7	1446 kWh	\$159.00	
LED	35	50,000 / 5.7	307 kWh	\$33.74	79%

LED FIXTURE INCLUDES:

- Two-Output Channel, Class 2 LED Driver, Model Number: AC-D18C350UVH
- Aluminum LED Driver Bracket
- 2 PCB LED Arrays with 28 Cree MX-3 LEDs



LED Fixture



WARRANTY

Texas Fluorescents warrants to the purchaser that this LED Fixture will be free from defects in material or workmanship for a period of 5 years from date of manufacture, when operated at a maximum ambient temperature of 110°F or 45°C, when properly installed and under normal conditions of use.


Item	Specification
Input Voltage	120-277V, 50/60Hz
LED CRI	75
Fixture CRI	76.4
LED Color Temperature	5000K
Fixture Color Temperature	5137
Fixture Lumens	2557 Lumen
Kit Lumens Outside Fixture	3501 Lumen
Lumen Maintenance	70% @ 5 years
Fixture Efficacy	73 Lumen/Watt
Zonal Lumen Requirement	0-40; 40% 40-70°; 40%
Warranty	5 Years
LED Quantity (Brand:Cree)	28
LED TMP Temperature @25°C	64.7°C
Input Power	35W
Driver Efficiency	88%
Power Factor @277V	0.999
THD@277V	8%
Driver TMP temp @25° Ambient	50.3°C
Noise	<24dB
EMI	FCC part 15
Max Operating Temperature	45°C Ambient
Min Operating Temperature	-40°C
LED Lighting Assembly Dimen	3.25"H x 12"Wx11"D

Tork 2107 Photocell

Approved For Use with AC LED Conversion Kits

- 120/277V 1800 VA Ballast Load
- 1 To 5 FC Turn On Light Level
- 3 To 15 FC Turn Off Light Level
- SPST Switch
- 16 AWG 6 Inch Wire Lead Terminal

- Temperature Rating -40 to 140°F
- 1/2" Conduit Mounting
- Not included, available from secondary sources





Catalog Number:
Notes: