

FEATURES & SPECIFICATIONS

INTENDED USE

A wrap around fluorescent fixture designed for parking garages, school corridors or any application where high abuse or vandalism could occur.

Construction

Back plate is die formed of 16 gauge steel. Lens attached to back plate with tamper resistant stainless steel screws.

Diffuser

Diffuser is made of injection molded UV stabilized 100% clear, polycarbonate with an internal prismatic pattern.

Mounting

Units may be surface or wall mounted.

Listing

Fixtures conform to Underwriters' Laboratories standards for production and are carefully tested prior to packing. Fixtures are UL Listed wet location for ceiling and damp location for wall mounting.



Electrical

Unless otherwise specified, ballasts are rapid start, class "P" thermally protected, H.P.F., CBM-ETL. Optional ballasts available include: energy saving (ESB), electronic (ELB), dimming (DIM), low temperature (CW). Standard voltage on all fixtures is 120V 60Hz AC, or as specified. Sufficient knockouts are provided on the back for all connections and through wiring.

ORDERING INFORMATION

Example: CV800 2328MV

CV800			232		MV			
Series	Lamp Count	Lamp Type & Tandem Code [2]			Ballast & Voltage [1]		Options [1]	
CV800	2	32	8	48" T8HO	MV	Electronic, Multivolt (120-277)	WP	6ft. 3 wire 18 gauge whip
				8 ft. Tandem (double lamp count)	X1	Wired for single ended LED T8 lamps	WP10	6ft. 4 wire 18 gauge whip
	2	F48T8HO	8	48" T8HO	X2	Wired for double ended LED T8 lamps	EM	Emergency ballast 500 lumens
				8 ft. Tandem (double lamp count)	XX	No sockets, ballasts or wiring	EM14	Emergency ballast 1400 lumens
							D	Ballast disconnect
							LN15W40	Single ended 15W 1800 Lumen 4000K* Included
							LN18W40	Single ended 18W 2100 Lumen 4000K* Included
							PI1	Wire harness, 3 wire

*Change 40 to 35 or 50 for 3500K or 5000K

