

FL Series

Spill Ring

FEATURES & SPECIFICATIONS

INTENDED USE

A beautiful combination of brushed nickel end caps and white bullnosed acrylic diffuser is perfect for residential or commercial applications. LED with electronic driver provides great light output through the bullnose diffuser. Brushed nickel metal endcaps add a deco contemporary style.

SIZE W x L x H in inches (mm)

5.70W x 24.50L x 4.50Dp


11.75W x 48.0L x 4.5Dp

CONSTRUCTION

All metal parts die formed from heavy gauge cold roll steel housing spot welded to insure uniformity and dimensional stability.

DIFFUSER

One piece .170 smooth opal 100% acrylic for a fully luminous light source.



TYPICAL OPTIONS AND ACCESSORIES

Whips, and lenses. See options page at the end of the T02SURF section, or contact factory for more details.

ORDERING INFORMATION

Example: FL24LS20W2000LDMV40KSN

2 FT

FL	24L	S20W2000L	DMV	40K	SN
Series	Size	Wattage and Lumen	Driver	Color Temperature	Finish
FL Spill Ring	24L 24.5"	S20W2000L 20 System Watts, 2000 Delivered Lumens S28W2700L 28 System Watts, 2700 Delivered Lumens H40W3800L 40 System Watts, 3800 Delivered Lumens	DMV 0-10V MV ? gfl - Half 120V-277V	30K 3000K 35K 3500K 40K 4000K 50K 5000K	SN Satin Nickel BZ Bronze

4 FT

Example: FL48LH72W7000LDMV40KSN

FL	48L	H72W7000L	DMV	40K	SN
Series	Size	Wattage and Lumen	Driver	Color Temperature	Finish
FL Spill Ring	48L 48"	S32W3450L 32 System Watts, 3450 Delivered Lumens S48W4800L 48 System Watts, 4800 Delivered Lumens S57W5400L 57 System Watts, 5400 Delivered Lumens H72W7000L 72 System Watts, 7000 Delivered Lumens	DMV 0-10V MV ? gfl - Half 120V-277V	30K 3000K 35K 3500K 40K 4000K 50K 5000K	SN Satin Nickel BZ Bronze

* Consult for more options

Catalog Number:
Notes: