

FEATURES & SPECIFICATIONS

INTENDED USE

Extremely low profile T8 strip for use with either remote ballasts or today's LED T8 lamps. Each fixture comes with an integral flex feed adapter. Easy mounting through provided holes in housing. Consult factory for optional reflectors and tandem configurations.

SIZE W x L x H in inches (mm)

- 2' 1.38" x 25.5" x 1.69"
- 3' 1.38" x 37.5" x 1.69"
- 4' 1.38" x 49.5" x 1.69"
- 5' 1.38" x 61.2" x 1.69"
- 6' 1.38" x 73.0" x 1.69"
- 8' 1.38 x 97.0" x 1.69"

LAMP

1 lamp position

MATERIALS & FEATURES

- Housing is die-formed and embossed code 22 gauge steel
- Finish is high reflectance baked white enamel
- Installed end feed connector accepts 3/8" steel flex conduit (available separately)
- Wired with 12' leads for instant start ballast operation
- Easy mounting through provided holes in housing
- Available for T8 13W, 14W, 15W, 17W, 25W, 32W or 40W linear fluorescent lamp in single and tandem lamp models
- Requires a remote ballast and enclosure (ordered separately)



MOUNTING

Surface mount

TYPICAL OPTIONS AND ACCESSORIES

Connector, whip, mounting and reflector options. Contact factory for more details.

ORDERING INFORMATION

LLS	1	32			X1	
Series	Lamp Count	Lamp Type [1]	Tandem Code [2]		Options [1]	
Narrow Body Strip	1	17	24 in. T8	5- 5ft. Tandem (24in & 36in, 2 lamp positions total)	FC	Flexconnect
	1	25	36 in. T8	6 - 6ft. Tandem (2 lamp positions total)	FCWP	Flexconnect + 6' whip
	1	32	48 in. T8	8 - 8ft. Tandem (2 lamp positions total)		
					Ballast & Voltage [1]	
					X	No Ballast
					X1	Wired for single ended LED lamp
					X2	Wired for double ended LED lamp

Example: LSS 132 X1

LED Lamp sold separately

Notes

[1] Tandem doubles length and lamp count. Same lamps in cross section, additional lamps end to end.

[2] Consult factory for reflector options.