

**FEATURES & SPECIFICATIONS**

**INTENDED USE**

Stylish ceiling/wall mounted luminaire in either white or walnut finish with a variety of lamp combinations and sizes enhanced by linear sided acrylic diffuser. Designed for baths, kitchens, rec rooms, corridors, aisles, stairwells, over or beside mirrors, over bulletin boards, in vanities, in displays.

**SIZE H x W in inches (mm)**

4.50"H x 5.62"W (115 x 145)  
Available in 24", 36" and 48" (610, 915, 1220) lengths

**LAMP**

2 lamp positions

**MOUNTING**

Back plate provided with adequate knockouts and mounting holes for either wall or ceiling installation.

**MATERIALS & FEATURES**

All metal parts are die formed from heavy gauge cold roll steel with overlapping end caps to insure uniformity and dimensional stability. One light and two light units same external dimensions.

**DIFFUSER**

Liner sided prismatic lens of extruded acrylic for controlled light.



**WIRING**

Standard ballast are 120volts, 60 hertz.

**LISTING**

**Fixture & Ballast:** UL Listed

**Ballast:** Thermally protected, class P, HPF, Non PCB

**TYPICAL OPTIONS AND ACCESSORIES**

Custom finishes, internal divider, front baffle, pull chains, convenience outlets, and emergency ballasts. CONTACT FACTORY for custom, compact fluorescent night light options, See options page at the end of the T02 WallF section, or contact factory for more details.

**ORDERING INFORMATION**

Example: LUT555MW228LTMVWH

<b>LUT555</b>	<b>MW</b>	<b>2</b>	<b>28</b>	<b>LT</b>	<b>MV</b>	<b>WH</b>
<b>Series</b>				<b>Divider &amp; Front Shield</b>		<b>Finish</b>
<b>LUT555</b> Lensed wall mount Up/down light				<b>Blank</b> No Divider or Front Shield <b>D</b> Divider <b>F</b> Front Shield Only <b>T</b> Top Shield Only <b>DF</b> Divider and Front Shield <b>TF</b> Top and Front Shield Both Divider and Front Shield REQUIRED for operation of up and down light. Dual ballasts are required for separate switching. Top and Front Shield REQUIRED for 100% down light		<b>WH</b> White (Standard) <b>OAK</b> Simulated Oak Painted Finish <b>WAS</b> Simulated Walnut painted finish <b>CH</b> Chrome <b>CHEND</b> Chrome finish on end caps only
<b>Lens Material</b>				<b>Ballast &amp; Voltage</b>		<b>Options [1]</b>
<b>A</b> Clear Prismatic acrylic <b>MW</b> Smooth white acrylic				<b>E120</b> Electronic, 120V <b>E277</b> Electronic 277V <b>MV*</b> Electronic, Multivolt (120-277) * Electronic Ballast ≤ 10%THP, Instant Start <b>LT</b> Lutron Dimming		<b>SW2</b> Pull chain, 2 way switching (Use with single ballasts) <b>GCO</b> Grounded convenience outlet (North American 3 prong) <b>EM</b> Emergency ballast, 500 lumens <b>EM14</b> Emergency ballast, 1100 lumens
<b>Lamp Count</b>				<b>Ballast Count</b>		
<b>2</b> (Lamps not included)				<b>Blank</b> Single Ballast <b>(11)</b> Dual One Lamp Ballasts		
<b>Lamp Type [1]</b>						
<b>17</b> 24 in. T8 <b>25</b> 36 in. T8 <b>32</b> 48 in. T8 <b>14</b> 24 in. T5 <b>21</b> 36 in. T5 <b>28</b> 48 in. T8 <b>24</b> 24 in. T5HO <b>39</b> 36 in. T5HO <b>54</b> 48 in. T5HO						

Catalog Number:
Notes:



T E X A S

F L U O R E S C E N T S

## LUT555 Series

Ceiling/Wall Mount Luminaire

Powered By Lutron®



Catalog Number:
-----------------

Notes:
--------