

RH Series

Outdoor Incandescent Remote Head



ILLUMINATION

- Smooth chrome-plated metallized reflector with plastic lens for optimal light distribution.
- Adjustable lamp heads with 6V and 12V wedge base incandescent lamps provide increased center-to-center spacing.

ELECTRICAL

- Powered from low voltage power source with low voltage wiring (not provided).

MOUNTING

- Universal mounting base mounts to single gang switch box.
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run.
- Suitable for wall or ceiling mount.


HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in gray or black finish.

WARRANTY / LISTING

- Five year warranty.

DIMENSIONS



FIXTURE COMPATIBILITY

Reference individual unit equipment specification sheets for remote load capacity availability.

MODEL TYPE	6V	12V	MODEL TYPE	6V	12V
NYDXR-50		X	TFX-2	X	
RMR-16-65	X		NYDXR-27	X	
RMR-16-125		X	EZXTE-RC	X	
R-5HO	X		CXTE-RC	X	
R-16-HO	X		DXR-125/1210		X
DXR-65/610	X		CALEDCXTE	X	
LEDCADXR	X				

ORDERING INFORMATION

Sample Part Number: **RH1-WP-12V9W**

MODEL	No. of HEADS	COLOR	HOUSING	VOLTAGE	WATTAGE ¹
RH	1 Single Head	Blank Gray	WP Weatherproof (standard)	6V	5.4W ²
	2 Double Head	B Black		12V	7.2W
					9.0W
					12W

¹ Wattage rating stated per head.

² Available in 6V units only.