



T E X A S

F L U O R E S C E N T S

Rectangle LED Flood Light

This compact, yet durable die-cast aluminum floodlight provides a flood of light from a single LED diode. Lighting Facts approved to provide 1500 lumens and 50,000 hours of life using 20 watts. It is an ideal replacement for a 50W HID. Die cast swivel are 1/2" NPS makes mounting simple to a standard junction box. Integrated heat fins, white reflector and tempered glass lens ensures optimum performance and suitable for wet location. Available in bronze or white finishes. Ideal applications for security, building facades, display signs and other residential outdoor flood or landscape lighting.



FEATURES AND CHARACTERISTICS

- Sturdy aluminum die cast housing and face frame
- Durable polyester powder coat finish
- Tempered glass lens
- Integrated heat fins for optimized heat dissipation
- White Reflector
- 1/2" NPS die casting swivel arm
- LED: Citizen CLL022-1204 with LM80 or Equivalent
- System Power Consumption: 20W
- Delivered Lumens: 1500 Lumens, Lighting Facts Approved
- Input Voltage: 120-277Vac 50/60 HZ
- 4000K Color Temperature
- Minimum starting temperature -22 Degrees F
- No Dimmable
- UL/CUL listed for Wet Locations
- Package 1 Piece per box, 12 Pieces Master Carton
- 5 Year Limited Warranty

ORDERING INFORMATION

Item No.	Description	Size
LFS46L20W1500LMV40KBZ	LED FLOOD SQ 20W 1500L MV 40K BZ	6"W x 4.75"H x 6"Ext
LFS46L20W1500LMV40KWH	LED FLOOD SQ 20W 1500L MV 40K WH	6"W x 4.75"H x 6"Ext

Catalog Number:
Notes: