

SHCRV Series

2 x 4
Direct/Indirect, Curve Diffuser, Surface Mount

INTENDED USE:

Specification grade, direct/indirect center diffuser luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings with surface mount configurations. Reflected light from matte surfaces provides a softened “sky light” appearance to the modern office environment. Unique dual curved.

SIZE W x L x H in inches (mm)

2 x 2 - 23.75W x 24.0L x 3.75Dp

2 x 4 - 23.75W x 48.0L x 3.75Dp

MATERIALS & FEATURES

Specially designed shroud alters recessed housing which is die-formed and embossed code 22 gauge steel to a surface mount fixture. Luminaire body finish is high reflectance baked white enamel, with matte white reflectors. Wiring knockouts are provided on the back of housing.

- Surface mount shroud changed recessed version to a surface mount version
- Center section is flush with outer panels, eliminating the dirt and debris from ceiling
- One piece enclosure is mounted to one piece doorframe
- Direct/indirect mimics “sky light” appearance
- Matte white reflective surfaces for soft, uniform light distribution



MOUNTING

Surface mount

ORDERING INFORMATION

STANDARD

Example: SHCRVPF24S32W3463LDMV40K

SHCRV	PF	24	S32W3463L	DMV	40K
Series		Size	Wattage and Lumen	Driver	Kelvin Temperature
SHCRV Direct/Indirect, Curve, surface mount		24 2 x 4	S32W3463L 32 System Watts, 3463 Delivered Lumens S48W4813L 48 System Watts, 4813 Delivered Lumens S57W5448L 57 System Watts, 5448 Delivered Lumens	DMV 0-10V MV ? gfl - Ha'f 120V-277V	35K 3500K 40K 4000K
Diffusers					Options
PF Perforated basket with overlay RL Ribbed linear lens					WP 6 ft. whip, 3/18 ga WP10 6 ft. whip, 4/18 ga

HIGH OUTPUT

SHCRV	PF	24	H70W7144L	DMV	40K
Series		Size	Wattage and Lumen	Driver	Kelvin Temperature
SHCRV Direct/Indirect, Curve, surface mount		24 2 x 4	H70W7144L 70 System Watts, 7144 Delivered Lumens	DMV 0-10V MV ? gfl - Ha'f 120V-277V	35K 3500K 40K 4000K
Diffusers					Options
PF Perforated basket with overlay RL Ribbed linear lens					WP 6 ft. whip, 3/18 ga WP10 6 ft. whip, 4/18 ga

Texas Fluorescents

2055 Luna Rd Suite 142 Carrollton TX 75006

Phone: 972-247-3171 Fax: 972-247-0200

www.texasfluorescents.com email: sales@texasfluorescents.com

Catalog Number:

Notes:

SHCRV Series

2 x 2

Direct/Indirect, Curve Diffuser, Surface Mount



ORDERING INFORMATION

Example: SHCRVPF22S24W2406LDMV40K

STANDARD

SHCRV	PF	22	S24W2406L	DMV	40K
Series SHCRV Direct/Indirect, Curve, surface mount	Diffusers PF Perforated basket with overlay RL Ribbed linear lens	Size 22 2 x 2	Wattage and Lumen S24W2406L 24 System Watts, 2406 Delivered Lumens S36W3811L 36 System Watts, 3811 Delivered Lumens S46W4650L 46 System Watts, 4650 Delivered Lumens	Driver DMV 0-10V MV ? g ^f l - Ha ^f 120V-277V	Kelvin Temperature 35K 3500K 40K 4000K
					Options WP 6 ft. whip, 3/18 ga WP10 6 ft. whip, 4/18 ga

HIGH OUTPUT

SHCRV	PF	MV	H67W7067L	DMV	40K
Series SHCRV Direct/Indirect, Curve, surface mount	Diffusers PF Perforated basket with overlay RL Ribbed linear lens	Size 22 2 x 2	Wattage and Lumen H67W7067L 67 System Watts, 7067 Delivered Lumens	Driver DMV 0-10V MV ? g ^f l - Ha ^f 120V-277V	Kelvin Temperature 35K 3500K 40K 4000K
					Options WP 6 ft. whip, 3/18 ga WP10 6 ft. whip, 4/18 ga

DIMENSIONS

All dimensions are inches. Specifications subject to change without notice.

