

INTENDED USE:

Specification grade, direct/indirect center diffuser luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings with surface mount configurations. Reflected light from matte surfaces provides a softened “sky light” appearance to the modern office environment. Unique dual curved.

SIZE W x L x H in inches (mm)

2 x 2 - 23.75W x 24.0L x 3.75Dp

4 x 4 - 23.75W x 48.0L x 3.75Dp

LAMP

2 lamp positions.

MATERIALS & FEATURES

Specially designed shroud alters recessed housing which is die-formed and embossed code 22 gauge steel to a surface mount fixture. Luminaire body finish is high reflectance baked white enamel, with matte white reflectors. Wiring knockouts are provided on the back of housing.

- Surface mount shroud changed recessed version to a surface mount version
- Center section is flush with outer panels, eliminating the dirt and debris from ceiling
- One piece enclosure is mounted to one piece doorframe
- Direct/indirect mimics “sky light” appearance
- Matte white reflective surfaces for soft, uniform light distribution

MOUNTING

Surface mount



LISTING

Fixture & Ballast: UL Listed

Ballast: Thermally protected, class P, HPF, Non PCB

TYPICAL OPTIONS AND ACCESSORIES

Emergency ballasts, whips, and lenses

Contact factory for additional options.

ORDERING INFORMATION

Example: SHCRVPF232MV

SHCRV	32	MV	GA	
Series	Lamp Count	Lamp Type	Ballast & Voltage	Options [1]
SHCRV Direct/Indirect, Curve, surface mount	2 Lamps Not included	32 24 in. T8 32 22 in. T5 24 22 in. T5HO 32 48 in. T8 28 26 in. T5 54 46 in. T5HO 40BX Biaxl (TT5) 2G11 4-Pin 40W	S Residential 120V Ballast MV Electronic, multivolt (120-277) H MV Electronic, Multivolt P MV Electronic Program Start (120-277) G MV Line or 0-10V dimming, multivolt	WP 6 ft. whip, 3/18 ga WP10 6 ft. whip, 4/18 ga EM Emergency ballast, 500 lumens EM14 Emergency ballast, 1400 lumens
	Diffusers			
	PF Perforated basket with overlay RL Ribbed linear lens			

Notes:

[1] Custom louvers available in any cell configurations. Consult factory for additional information.

[2] Hi-Lume and Lo-Lume ballasts available for T8 lamps only

[3] Consult factory for custom finishes

[4] Magnetic & Electronic T12 ballasts drive a 34W energy saver lamp

Note:EM14 ballast required for T5 & T5HO lamps

DIMENSIONS

All dimensions are inches. Specifications subject to change without notice.

