

## FEATURES & SPECIFICATIONS

- Heavy Duty Die Cast Aluminum Housing
- Tempered Glass Lens
- Die Cast Hinged Front & Rear Housings, Gasket Coin Plugs on Sides and Back
- Built-In Template for Mounting to Electrical Box
- Size: 18.0W x 7.35H x 9.0D
- Bronze Powder Coat Finish
- One Piece Anodized Aluminum Reflector
- Porcelain Socket & Bracket
- Meets Local "Dark Sky" Requirements
- Excellent for Use as an Uplight
- Lamps Included
- UL Listed (wet location)



## ORDERING INFORMATION


EX: SM302 150HP SMTLP

Item No.	Dimensions (LxWxH)	Lamping
SM302150HPSMTLP	18" x 7,25" x 9.0"	150W HPS
SM302150MHMTLP	18" x 7,25" x 9.0"	150W MH
SM3021PL42MVLP	18" x 7,25" x 9.0"	42W TTT
SM3021PL42MVLPEM	18" x 7,25" x 9.0"	42W TTT
SM302L42W3424L50K	18" x 7,25" x 9.0"	32 CREE LED 42W, 3424 Lumens, 5000K

\*Emergency ballast fits inside unit.

\*\*DLC Certified

## Accessories:

Description	Model #	Image
Photocell 120V	CAT. # PC120	
Photocell 277V	CAT.# PC277	




### LED vs. HID WALL PACK

Wall Pack Light Source	Input Wattage	Lifespan Hrs/Yrs	Energy Use (24hrs/day) Annual	Annual Cost (maintenance + electricity) @ 50.11 / kWh	Electrical Cost Savings
HID	165	24,000 / 2.7	1446 kWh	\$159.00	
LED	42	50,000 / 5.7	368 kWh	\$40.49	74%



**LED Array**



### LED FIXTURE INCLUDES:

- Two-Output Channel, Class 2 LED Driver, Model Number: AC-D18C350UVH
- Aluminum LED Driver Bracket
- 2 PCB LED Arrays with 32 Cree MX-3 LEDs

### WARRANTY

Texas Fluorescents warrants to the purchaser that this LED Fixture will be free from defects in material or workmanship for a period of 5 years from date of manufacture, when operated at a maximum ambient temperature of 110°F or 45°C, when properly installed and under normal conditions of use.

Item	Specification
Input Voltage	120-277V, 50/60Hz
LED CRI	75
Fixture CRI	73.5
LED Color Temperature	5000K
Fixture Color Temperature	5412
Fixture Lumens	2476 Lumen
Kit Lumens Outside Fixture	3501 Lumen
Lumen Maintenance	70% @ 5 years
Fixture Efficacy	56.20 Lumen/Watt
Zonal Lumen Requirement	0-90; 100% 80-90 <10%
Warranty	5 Years
LED Quantity (Brand:Cree)	32
LED TMP Temperature @25°C	74.5°C
Input Power	44W
Driver Efficiency	88%
Power Factor @277V	0.954
THD@277V	14.86%
Driver TMP temp @25° Ambient	55.6°C
Noise	<24dB
EMI	FCC part 15
Max Operating Temperature	45°C Ambient
Min Operating Temperature	-40°C
LED Lighting Assembly Dimen	11.375"H x 9.55"Wx6.758"D

### Tork 2107 Photocell

#### Approved For Use with AC LED Conversion Kits

- 120/277V 1800 VA Ballast Load
- 1 To 5 FC Turn On Light Level
- 3 To 15 FC Turn Off Light Level
- SPST Switch
- 16 AWG 6 Inch Wire Lead Terminal
- Temperature Rating -40 to 140°F
- 1/2" Conduit Mounting
- Not included, available from secondary sources

