

### FEATURES & SPECIFICATIONS

#### INTENDED USE

Specification grade, dual lamp strip for interior coves, valances and displays requiring lighting without dark areas at lamp ends. Mini body style. Fixture telescopes to maintain a uniform distribution of light especially

#### SIZE: W x L x H in inches (mm)

2.5W x 1.25H (63 x 32)

Fixture length defined in ordering table below.

#### LAMP

2 lamp positions

#### MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gauge steel. Finish is high reflectance baked white enamel. Wiring knockouts are provided on back and end of housing. Fully open, fixture stagger is as follows: 2'=10", 3'=20", 4'=26"

- Mini body style for areas with minimum clearance
- Available with T5 or T8 lamp styles
- Offset provides continuous row lighting

#### MOUNTING

Surface mount or suspended



#### LISTING

Fixture and Ballast: UL Listed

Ballast: Thermally protected, class P, HPF, Non PCB; unless specified otherwise.

#### TYPICAL OPTIONS AND ACCESSORIES

Whips, fuses and cored sets. See options page at the end of the T02 Strip section or contact factory for more details.

### ORDERING INFORMATION

### EXAMPLE: TSSKD214E120WP

| TSSKD        |          | (Lamps not included)                          |  | Ballast / Voltage |                                     | Options [1]    |   |
|--------------|----------|---|--|-------------------|-------------------------------------|----------------|---|
| Series       | Lamp #   | Lamp Type [1]                                 |  |                   |                                     |                |   |
| <b>TSSKD</b> | <b>2</b> | <b>14</b> 14W T5 Fixture Length = 26.5 in.    |  | <b>MV</b>         | Electronic, Multivolt (120-277)     | <b>WP</b>      | 6 ft. 3 wire 18 gauge whip                  |
|              | <b>2</b> | <b>21</b> 21W T5 Fixture Length = 38.25 in.   |  |                   |                                     | <b>CS</b>      | 8 ft. 3/18 3 prong (5-15P)                  |
|              | <b>2</b> | <b>28</b> 28W T5 Fixture Length = 50.0 in.    |  | <b>HMV [2]</b>    | Electronic, Multivolt, Hi-Lume      |                | cord & plug                                 |
|              | <b>2</b> | <b>35</b> 35W T5 Fixture Length = 62.0 in.    |  | <b>LMV [2]</b>    | Electronic, Multivolt, Lo-Lume      | <b>LN15W30</b> | Single ended 15W 1800 Lumen 3500K* Included |
|              | <b>2</b> | <b>24</b> 24W T5HO Fixture Length = 26.5 in.  |  | <b>X1</b>         | Wired for single ended LED T8 lamps | <b>LN18W30</b> | Single ended 18W 2100 Lumen 3500K* Included |
|              | <b>2</b> | <b>39</b> 39W T5HO Fixture Length = 38.25 in. |  | <b>X2</b>         | Wired for double ended LED T8 lamps |                |   |
|              | <b>2</b> | <b>54</b> 54W T5HO Fixture Length = 50.0 in.  |  | <b>XX</b>         | No sockets, ballasts or wiring      |                |   |
|              | <b>2</b> | <b>80</b> 80W T5HO Fixture Length = 62.0 in.  |  |                   |                                     |                | * Change 30 to 40 or 50 for 4000K or 5000K  |
|              | <b>2</b> | <b>17</b> 17W T8 Fixture Length = 28.0 in.    |  |                   |                                     |                |   |
|              | <b>2</b> | <b>25</b> 25W T8 Fixture Length = 40.0 in.    |  |                   |                                     |                |   |
|              | <b>2</b> | <b>32</b> 32W T8 Fixture Length = 52.0 in.    |  |                   |                                     |                |   |

#### NOTE:

[1] See end of T02Strip section for many additional lamps, ballasts, finishes and options.

[2] HiLume and LoLume ballasts available for T8 lamps only

[3] EM for T5, T5HO requires T5 emergencies