



T E X A S

F L U O R E S C E N T S

UCLL 1x4 ft.

LED Low Profile Center Basket
Recessed or Surface Mount

FEATURES & SPECIFICATIONS

INTENDED USE

Low profile LED center lens fixtures are ideal for shallow plenum spaces. Specification grade, direct / indirect center diffuser appearance luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings with recessed configurations. Reflected light from matte surfaces provide a softened “sky light” appearance to the modern office environment. Linear ribbed lens encloses the LED array and is designed to maximize efficiency and minimize glare.

SIZE W x L x H in inches

11.7”W x 47.8”L x 3.25”D

MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gage steel. Luminaire body finish is high reflectance baked white enamel, with matte white re-reflectors. Wiring knockouts are provided on the back of housing. Center diffuser snaps into place; no tools are required for removal. Diffuser is ribbed acrylic lens provides increased light output.

- Direct / indirect mimics “sky light” appearance
- Matte white reflective surfaces for soft, uniform light distribution



Specially designed lens (LL) for LED Array to provide enhanced light transmission while minimizing glare and LED diode shadows.

MOUNTING

Recessed inverted T-Bar ceilings. Grid mount or Surface Mount.

ORDERING INFORMATION

Example: UCLL14L21W2032LDMV40K

STANDARD

UC	LL	14L	S21W2032L	DMV	40K
Series	Lens Material	Size	Wattage / Lumen	Driver	Color Temperature
UC Center Basket Grid Mount	LL Linear Ribbed Lens	14L	S21W2032L 21 System Watts, 2171 Delivered Lumens S28W2563L 28 System Watts, 2563 Delivered Lumens	DMV 0-10V Dimming MV Multi Volt 120-277V	35K 3500K 40K 4000K
SHUC Center Basket Surface Mount					

HIGH OUTPUT

UC	LL	14L	H40W3798L	DMV	40K
Series	Lens Material	Size	Wattage / Lumen	Driver	Color Temperature
UC Center Basket Grid Mount	LL Linear Ribbed Lens	14L	H30W3068L 30 System Watts, 3025 Delivered Lumens H40W3798L 40 System Watts, 3798 Delivered Lumens	DMV 0-10V Dimming MV Multi Volt 120-277V	35K 3500K 40K 4000K
SHUC Center Basket Surface Mount					

* Consult FACTORY for more options

Catalog Number:
Notes:



T E X A S

F L U O R E S C E N T S

UCLL 2x2 ft.

LED Low Profile Center Basket
Recessed or Surface Mount

FEATURES & SPECIFICATIONS

INTENDED USE

Low profile LED center lens fixtures are ideal for shallow plenum spaces. Specification grade, direct / indirect center diffuser appearance luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings with recessed configurations. Reflected light from matte surfaces provide a softened “sky light” appearance to the modern office environment. Linear ribbed lens encloses the LED array and is designed to maximize efficiency and minimize glare.

SIZE W x L x H in inches

24”W x 24”L x 3.25”D

MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gage steel. Luminaire body finish is high reflectance baked white enamel, with matte white re-flectors. Wiring knockouts are provided on the back of housing. Center diffuser snaps into place; no tools are required for removal. Diffuser is ribbed acrylic lens provides increased light output.

- Direct / indirect mimics “sky light” appearance
- Matte white reflective surfaces for soft, uniform light distribution



Specially designed lens (LL) for LED Array to provide enhanced light transmission while minimizing glare and LED diode shadows.

MOUNTING

Recessed inverted T-Bar ceilings. Grid mount or Surface Mount.

ORDERING INFORMATION STANDARD

UC	LL	14L	S21W2032L	DMV	40K	
Series	Lens Material	Size	Wattage / Lumen		Driver	Color Temperature
UC Center Basket Grid Mount	LL Linear Ribbed Lens	14L	S21W2032L 21 System Watts, 2171 Delivered Lumens S28W2563L 28 System Watts, 2563 Delivered Lumens		DMV 0-10V Dimming MV Multi Volt 120-277V	35K 3500K 40K 4000K
SHUC Center Basket Surface Mount						

HIGH OUTPUT

UC	LL	14L	H40W3798L	DMV	40K	
Series	Lens Material	Size	Wattage / Lumen		Driver	Color Temperature
UC Center Basket Grid Mount	LL Linear Ribbed Lens	14L	H30W3068L 30 System Watts, 3025 Delivered Lumens H40W3798L 40 System Watts, 3798 Delivered Lumens		DMV 0-10V Dimming MV Multi Volt 120-277V	35K 3500K 40K 4000K
SHUC Center Basket Surface Mount						

* Consult FACTORY for more options

Catalog Number:
Notes:



T E X A S

F L U O R E S C E N T S

UCLL 2x4 ft.

LED Low Profile Center Basket
Recessed or Surface Mount

FEATURES & SPECIFICATIONS

INTENDED USE

Low profile LED center lens fixtures are ideal for shallow plenum spaces. Specification grade, direct / indirect center diffuser appearance luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings with recessed configurations. Reflected light from matte surfaces provide a softened "sky light" appearance to the modern office environment. Linear ribbed lens encloses the LED array and is designed to maximize efficiency and minimize glare.

SIZE W x L x H in inches

24"W x 48"L x 3.25"D

MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gage steel. Luminaire body finish is high reflectance baked white enamel, with matte white re-reflectors. Wiring knockouts are provided on the back of housing. Center diffuser snaps into place; no tools are required for removal. Diffuser is ribbed acrylic lens provides increased light output.



Specially designed lens (LL) for LED Array to provide enhanced light transmission while minimizing glare and LED diode shadows.

MOUNTING

Recessed inverted T-Bar ceilings. Grid mount or Surface Mount.

- Matte white reflective surfaces for soft, uniform light distribution

ORDERING INFORMATION

Example: UCLL24LS32W3463LDMV40K

STANDARD

UC	LL	24L	S32W3463L	DMV	40K
Series	Lens Material	Size	Wattage and Lumen		Color Temperature
UC Center Basket Grid Mount	LL Linear Ribbed Lens	24L	S32W3463L 32 System Watts, 3463 Delivered Lumens	DMV 0-10V Dimming MV Multi Volt 120-277V	35K 3500K 40K 4000K
SHUC Center Basket Surface Mount			S48W4813L 48 System Watts, 4813 Delivered Lumens		
			S57W5448L 57 System Watts, 5448 Delivered Lumens		

HIGH OUTPUT

UC	LL	24L	H72W6994L	DMV	40K
Series	Lens Material	Size	Wattage and Lumen		Color Temperature
UC Center Basket Grid Mount	LL Linear Ribbed Lens	24L	H72W6994L 72 System Watts, 6994 Delivered Lumens	DMV 0-10V Dimming MV Multi Volt 120-277V	35K 3500K 40K 4000K
SHUC Center Basket Surface Mount					

Consult FACTORY for more options

Catalog Number:
Notes: