

USI 1204

Smoke & Fire Alarm



* picture may not resemble actual product

120 Volt AC Powered with Silencer and Battery Backup, Ionization, includes Dust Cover and Battery Pull-Tab



FEATURES & SPECIFICATIONS

- Battery Pull-Tab - activates battery and reduces installation time.
- 9V Battery backup in Event of AC Power Failure
- Super Heavy Duty Battery Included - warranted for 3 years from date of original installation
- Dust Cover - full dust and contaminant cover - protects the smoke alarm from spray applications, thereby eliminating the need to remove the alarm during home construction
- Silencer Feature - convenient silencer button with automatic reset allows you to temporarily override alarm - ideal for cooking smoke and fireplaces - eliminates nuisance alarms
- Ideal for Replacement of Most Existing Smoke Alarms
- Interconnectable up to 18 units - when unit goes into alarm, all interconnected units sound their alarm.
- Originating Alarm Feature - when smoke is detected, the red LED flashes on the initiating smoke alarm
- Green LED Indicator for AC Power
- Separate Large Size Mounting Plate Attaches to any Standard Rectangular or Octagon Junction Box and Covers Drywall Cutout - for easy installation and coverage of drywall cutouts.
- Loud 85 Decibel Horn
- Low Battery Audible Indicator
- 120 VAC (60 Hz) Power
- Wire Harness for Easy Connection
- Chamber and Cover Designs Protect Alarm from bugs and Contaminants.
- 5 Year Limited Warranty
- UTHA/UL Listed

USI-1204					
	Size		Weight		Cube
	English (inches)	metric (mm)	lbs.	kg.	
Giftbox	5.5" x 5.5" x 1.75"	139 x 139 x 44	.60	0.3	-----
Master Carton (24 pcs)	12" x 12" x 12"	317 x 317 x 317	14	6.0	1.05 ft.